

TRADEMARK ASSIGNMENT

Electronic Version v1.1
 Stylesheet Version v1.1

SUBMISSION TYPE:	NEW ASSIGNMENT		
NATURE OF CONVEYANCE:	CHANGE OF NAME		
CONVEYING PARTY DATA			
Name	Formerly	Execution Date	Entity Type
Progress Paint Mfg. Co.		07/01/2005	CORPORATION: KENTUCKY
RECEIVING PARTY DATA			
Name:	Progress Paint Manufacturing Company Inc.		
Doing Business As:	DBA Progress Paint Manufacturing Company Inc.		
Street Address:	201 East Market Street		
City:	Louisville		
State/Country:	KENTUCKY		
Postal Code:	40202		
Entity Type:	CORPORATION: KENTUCKY		
PROPERTY NUMBERS Total: 3			
Property Type	Number	Word Mark	
Registration Number:	2700234	PROGRESS PROFESSIONAL	
Registration Number:	2700233	GRAYSEAL	
Registration Number:	2700271	PROGRESS INDUSTRIAL	
CORRESPONDENCE DATA			
Fax Number:	(502)584-2318		
	<i>Correspondence will be sent via US Mail when the fax attempt is unsuccessful.</i>		
Phone:	502 587-3183		
Email:	bdonald@tilfordlaw.com		
Correspondent Name:	Robert A. Donald, III		
Address Line 1:	401 West Main Street		
Address Line 2:	Suite 1400		
Address Line 4:	Louisville, KENTUCKY 40202		
NAME OF SUBMITTER:	Robert A. Donald, III		
Signature:	/Robert A. Donald, III/		

OP \$90.00 2700234

Date:

07/29/2008

Total Attachments: 1
source=Label#page1.tif

LINE RIOR

PROGRESS PROFESSIONAL

4000

Semi-Gloss Latex Enamel For Walls & Trim Old Parchment #4207

ONE U.S. GALLON - 3.79 LITERS

Basic Use And Information

4000 Semi-Gloss is a good choice where a durable, semi-gloss, dirt resistant finish is desired. Formulated for the professional painter, 4000 Semi-Gloss is a multi-purpose base enamel for use on exterior wood, drywall, plaster, masonry and metal. 4000 Semi-Gloss has low odor and forms a washable, durable and chip resistant finish. Ideal for institutional and residential use, any place a semi-gloss enamel is desired. **Instructions:** Do not apply when the surface or room temperature is below 50°F.

Technical Information

Recommended Film Thickness: Primer: Water
Dry: 1.4 mils. Wet: 4.3 mils.
Freeze-Thaw Stability: Protect from freezing.
Suggested Spread Rate: 300-325 sq. ft. per gallon on new surfaces.
Maximum V.O.C.: 3.1 lbs./gal.
Drying Time: 30 minutes to touch. May be recoated in 1 hour.

Surface Preparation

Surfaces must be dry and free of grease, wax, dirt and other foreign matter. Sand, caulk or fill all voids. Scrape off all loose paint. Roll the gloss on enamel on previously finished surfaces with an application of Progress Paint Prep, or by sanding. Measure or test surfaces with rag after sanding. Prime any water marks, cracks and discolored areas with a stain killer.

Unpainted Woodwork: Countersink and putty nailheads. Apply a prime coat of 4000 Enamel Undercoat. Between coats, lightly sand (steel wool) and then prime with Semi-Gloss Primer. Do not use oil based primers. **Unpainted Cement Block and Masonry:** Make sure new mortar is dry. 4000 Semi-Gloss may be applied directly to concrete block; however, 4000 D Primer should be used on masonry. **Unpainted Metal:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. Heavy metal or metal subject to rust, should be primed with Semi-Gloss Primer. Do not use oil based primers. **Unpainted Brick:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Plaster:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Drywall:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Metal:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Brick:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Plaster:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss. **Unpainted Drywall:** Clean, sand, prime and finish with 4000 Enamel Undercoat before applying 4000 Semi-Gloss.

Application

4000 Semi-Gloss is designed to be applied with any good quality paint applicator. It is not recommended to use a brush. For best results, use a roller. However, care should be taken not to spread the paint too thin. The paint should be applied in a corner. As with all common tinted paints, intermediate coats of the same color to assure color uniformity. **Method of Application:** Brush, 3/8" rag roller or spray. **Thinning:** Use 4000 Semi-Gloss as it comes from the can. If thinning is required, use no more than one-half pint of water per gallon. **Clean Up:** Clean equipment with soap and water immediately after use.

Maintenance

Allow painted surfaces to cure a minimum of 14 days before washing. Surfaces painted with 4000 Semi-Gloss may be washed with mild detergents or cleaners. Do not use abrasive cleaners.

Satisfaction Guarantee: Progress Paint warrants this paint to perform to customer's satisfaction when applied in accordance with label instructions over a properly prepared surface. If this paint does not perform as warranted, return the unused portion of this paint and the color sample to the place of purchase, and the dealer will either refund your money or replace the paint. This warranty does not cover the cost of labor for the application or removal of any paint.

PROGRESS PAINT MANUFACTURING COMPANY INC. LOUISVILLE, KY 40202

TRADEMARK

REEL: 003824 FRAME: 0270

RECORDED: 07/29/2008